

SAFETY DATA SHEET

Version 5.7
Revision Date 05/24/2016
Print Date 03/18/2017

1. PRODUCT AND COMPANY IDENTIFICATION**1.1 Product identifiers**

Product name : Acetic acid

Product Number : 537020
Brand : Sigma-Aldrich
Index-No. : 607-002-00-6

CAS-No. : 64-19-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832
Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 3), H226
Skin corrosion (Category 1A), H314
Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H226

Flammable liquid and vapour.

H314

Causes severe skin burns and eye damage.

Precautionary statement(s)

P210

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242

Use only non-sparking tools.

P243

Take precautionary measures against static discharge.

P264

Wash skin thoroughly after handling.

P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P330 + P331 P303 + P361 + P353	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see supplemental first aid instructions on this label).
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Synonyms	: Glacial acetic acid
Formula	: C ₂ H ₄ O ₂
Molecular weight	: 60.05 g/mol
CAS-No.	: 64-19-7
EC-No.	: 200-580-7
Index-No.	: 607-002-00-6
Registration number	: 01-2119475328-30-XXXX

Hazardous components

Component	Classification	Concentration
Acetic acid		
	Flam. Liq. 3; Skin Corr. 1A; Eye Dam. 1; H226, H314, H318	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Moisture sensitive.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Acetic acid	64-19-7	TWA	10.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Pulmonary function Upper Respiratory Tract irritation Eye irritation		

		STEL	15.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Pulmonary function Upper Respiratory Tract irritation Eye irritation		
		ST	15.000000 ppm 37.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
		Can be found in concentrations of 5-8% in vinegar		
		TWA	10.000000 ppm 25.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
		Can be found in concentrations of 5-8% in vinegar		
		TWA	10.000000 ppm 25.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		The value in mg/m3 is approximate.		
		TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Pulmonary function Upper Respiratory Tract irritation Eye irritation		
		STEL	15 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Pulmonary function Upper Respiratory Tract irritation Eye irritation		
		TWA	10 ppm 25 mg/m3	USA. NIOSH Recommended Exposure Limits
		Can be found in concentrations of 5-8% in vinegar		
		ST	15 ppm 37 mg/m3	USA. NIOSH Recommended Exposure Limits
		Can be found in concentrations of 5-8% in vinegar		
		TWA	10 ppm 25 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		The value in mg/m3 is approximate.		
		PEL	10 ppm 25 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	15 ppm 37 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		C	40 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

Derived No Effect Level (DNEL)

Application Area	Exposure routes	Health effect	Value
Workers	Inhalation	Acute local effects	25 mg/m3
Workers	Inhalation	Long-term local effects	25 mg/m3
Workers	Skin contact	Long-term local effects	10mg/kg BW/d
Consumers	Inhalation	Acute local effects	25 mg/m3
Consumers	Inhalation	Long-term local effects	25 mg/m3

Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0.478 mg/kg

Marine water	0.3058 mg/l
Fresh water	3.058 mg/l
Marine sediment	1.136 mg/kg
Fresh water sediment	11.36 mg/kg
Sewage treatment plant	85 mg/l
Aquatic intermittent release	30.58 mg/l

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nature latex/chloroprene

Minimum layer thickness: 0.6 mm

Break through time: 32 min

Material tested: Lapren® (KCL 706 / Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- | | |
|--------------------|------------------------------------|
| a) Appearance | Form: liquid
Colour: colourless |
| b) Odour | pungent |
| c) Odour Threshold | No data available |

d) pH	2.4 at 60.05 g/l
e) Melting point/freezing point	Melting point/range: 16.2 °C (61.2 °F) - lit.
f) Initial boiling point and boiling range	117 - 118 °C (243 - 244 °F) - lit.
g) Flash point	No data available
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 19.9 %(V) Lower explosion limit: 4 %(V)
k) Vapour pressure	73.3 hPa (55.0 mmHg) at 50.0 °C (122.0 °F) 15.2 hPa (11.4 mmHg) at 20.0 °C (68.0 °F)
l) Vapour density	No data available
m) Relative density	1.049 g/cm ³ at 25 °C (77 °F)
n) Water solubility	completely miscible
o) Partition coefficient: n-octanol/water	log Pow: -0.17
p) Auto-ignition temperature	485.0 °C (905.0 °F)
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

Surface tension	28.8 mN/m at 10.0 °C (50.0 °F)
-----------------	--------------------------------

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Oxidizing agents, Soluble carbonates and phosphates, Hydroxides, Metals, Peroxides, permanganates, e.g. potassium permanganate, Amines, Alcohols, Nitric acid

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 3,310 mg/kg

LC50 Inhalation - Mouse - 1 h - 5620 ppm

Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Conjunctive irritation. Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Other. Blood:Other changes.

LC50 Inhalation - Rat - 4 h - 11.4 mg/l

LD50 Dermal - Rabbit - 1,112 mg/kg

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Causes severe burns.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Corrosive to eyes

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: AF1225000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Ingestion or inhalation of concentrated acetic acid causes damage to tissues of the respiratory and digestive tracts. Symptoms include: hematemesis, bloody diarrhea, edema and/or perforation of the esophagus and pylorus, pancreatitis, hematuria, anuria, uremia, albuminuria, hemolysis, convulsions, bronchitis, pulmonary edema, pneumonia, cardiovascular collapse, shock, and death. Direct contact or exposure to high concentrations of vapor with skin or eyes can cause: erythema, blisters, tissue destruction with slow healing, skin blackening, hyperkeratosis, fissures, corneal erosion, opacification, iritis, conjunctivitis, and possible blindness., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Acetic acid	64-19-7	1993-04-24

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Acetic acid	64-19-7	1993-04-24

New Jersey Right To Know Components

	CAS-No.	Revision Date
Acetic acid	64-19-7	1993-04-24

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eye Dam.	Serious eye damage
Flam. Liq.	Flammable liquids
H226	Flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
Skin Corr.	Skin corrosion

HMIS Rating

Health hazard:	3
Chronic Health Hazard:	*
Flammability:	2
Physical Hazard	0

NFPA Rating

Health hazard:	3
Fire Hazard:	2
Reactivity Hazard:	0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information
Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956

Version: 5.7

Revision Date: 05/24/2016

Print Date: 03/18/2017